

# TECHNICAL DATASHEET

Art.Nr. KUD-0314-C1230g  
Version from 13.12.2017  
Page 1 of 1

Time Out Art.-Nr.: KUD-0314-C1230      Art.-description: Unidirectional Carbon-314g/m<sup>2</sup>-1230mm

## Textile Structure

### ARTICLE CONSTRUCTION (following EN 13473-1)

Layers	Konstruktion	Areaweight	Tolerance	Material
2	0°	300g/m <sup>2</sup>	+/- 5,0 %	ZOLTEK PANEX 35-13 50K
1	85°	11g/m <sup>2</sup>	+/- 5,0 %	E-Glass 68 tex
Stitching		3g/m <sup>2</sup>	+/- 1 g/m <sup>2</sup>	PES [Polyester] 33 dtex SC

### FURTHER CHARACTERISTICS

Stitching refinement :	5,0	Wrapping :	Trikot	Width (nominal):	1.230 mm
Stitching length:	5,00 mm	Total tolerance:	5,3%	Total area weight:	314 g/m <sup>2</sup>

Packaging (standard)      Each roll is wound on a cardboard tube and wrapped in a plastic film.  
Further packaging options can be offered individually.

Storing demands      If in original packaging: no humidity nor direct sunlight. To avoid problems with humidity or electrostatic charging: 24 hours before application the multiaxial fibers should be conditioned to the equivalent working areas.