

SD 5502 - 1064



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SD 5502

Product code : 1064.

Hardener for epoxy resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Hardener for epoxy resin

Uses advised against : data not available

1.3. Details of the supplier of the safety data sheet

Registered company name : SICOMIN Composites.

Address : 31 avenue de la Lardiere - BP 23.13161.Chateauneuf les Martigues.France.

Telephone : +33 (0)4 42 42 30 20. Fax : +33 (0)4 42 81 29 29.

e-mail: composites@sicomin.com

Site web : <http://www.sicomin.com>

1.4. Emergency telephone number : .

Association/Organisation : INRS / ORFILA tél: +33(0)1.45.42.59.59 - (FRANCE) .

Other emergency numbers

Health and Safety Executive (HSE) Chemicals Regulation Directorate - Telephone: +44 151 951 3317 - USA : +1/ 800/ 424.9300

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Acute dermal toxicity, Category 4 (Acute Tox. 4, H312).

Skin corrosion, Category 1B (Skin Corr. 1B, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07



GHS05



GHS09

Signal Word :

DANGER

Product identifiers :

EC 220-666-8

EC 500-105-6

CAS 1293368-66-7

EC 216-032-5

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE

POLYALKYL AMINES

FORMALDEHYDE, POLYMERS WITH DIETHYLENETRIAMINE AND STYRENATED PHENOL

META XYLENE DIAMINE

SD 5502 - 1064

EC 262-975-0 PHENOL, STYRENATED
EC 268-626-9 POLYETHYLENEPOLYAMINES
EC 223-775-9 3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE

Hazard statements :

H302 + H312 Harmful if swallowed or in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 2855-13-2 EC: 220-666-8 REACH: 01-2119514687-32-XXXX 3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCL OHEXYLAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412		25 <= x % < 50
CAS: 39423-51-3 EC: 500-105-6 REACH: 01-2119556886-20-XXXX POLYALKYL AMINES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411		25 <= x % < 50
CAS: 1293368-66-7 FORMALDEHYDE, POLYMERS WITH DIETHYLENETRIAMINE AND STYRENATED PHENOL	GHS05, GHS07 Dgr Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318		2.5 <= x % < 10
CAS: 9046-10-0 EC: 618-561-0 REACH: 01-2119557899-12-XXXX REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1,2-DIOL WITH AMMONIA	GHS05 Dgr Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412		2.5 <= x % < 10

SD 5502 - 1064

CAS: 2579-20-6 EC: 219-941-5 REACH: 01-2119543741-41-XXXX 1,3-CYCLOHEXYLENEBIS (METHYLAMINE)	GHS07, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412		2.5 <= x % < 10
CAS: 1477-55-0 EC: 216-032-5 REACH: 01-2119480150-50-XXXX META XYLENE DIAMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 4, H332 Aquatic Chronic 3, H412	[1]	2.5 <= x % < 10
CAS: 61788-44-1 EC: 262-975-0 PHENOL, STYRENATED	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411		1 <= x % < 2.5
CAS: 68131-73-7 EC: 268-626-9 REACH: 01-2119485823-28-XXXX POLYETHYLENEPOLYAMINES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		1 <= x % < 2.5
CAS: 69-72-7 EC: 200-712-3 REACH: 01-2119486984-17-XXXX ACIDE SALICYLIQUE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318		1 <= x % < 2.5
CAS: 4067-16-7 EC: 223-775-9 REACH: 01-219485826-22-XXXX 3,6,9,12-TETRA-AZATETRADECAMETHYLE NEDIAMINE	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411		0 <= x % < 1

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

If inhaled, move the patient to fresh air and keep warm and rest.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

SD 5502 - 1064

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor :

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.

Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.

Wear conform with the European standard EN 469.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

SD 5502 - 1064

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep away from food and drink, including those for animals.

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.

Keep container tightly closed in a dry place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Hardener

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1477-55-0			0,1 mg/m3	Skin	

- France (INRS - ED984 :2012) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1477-55-0	-	-	-	0.1	-	-

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Workers.

Dermal contact.

Long term systemic effects.

0.91 mg/kg body weight/day

Dermal contact.

SD 5502 - 1064

Potential health effects: DNEL :	Long term local effects. 0.044 mg of substance/cm2
Exposure method: Potential health effects: DNEL :	Inhalation. Short term systemic effects. 8550 mg of substance/m3
Exposure method: Potential health effects: DNEL :	Inhalation. Long term systemic effects. 1.59 mg of substance/m3
Final use:	Consumers.
Exposure method: Potential health effects: DNEL :	Ingestion. Short term systemic effects. 32 mg/kg body weight/day
Exposure method: Potential health effects: DNEL :	Ingestion. Long term systemic effects. 0.65 mg/kg body weight/day
Exposure method: Potential health effects: DNEL :	Dermal contact. Short term systemic effects. 13 mg/kg body weight/day
Exposure method: Potential health effects: DNEL :	Dermal contact. Short term local effects. 1.59 mg of substance/cm2
Exposure method: Potential health effects: DNEL :	Dermal contact. Long term systemic effects. 0.4 mg/kg body weight/day
Exposure method: Potential health effects: DNEL :	Dermal contact. Long term local effects. 0.68 mg of substance/cm2
Exposure method: Potential health effects: DNEL :	Inhalation. Short term systemic effects. 2542 mg of substance/m3
Exposure method: Potential health effects: DNEL :	Inhalation. Long term systemic effects. 0.46 mg of substance/m3

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Final use:	Workers.
Exposure method: Potential health effects: DNEL :	Dermal contact. Long term systemic effects. 0.91 mg/kg body weight/day
Exposure method: Potential health effects: DNEL :	Dermal contact. Long term local effects. 0.44 mg of substance/cm2

SD 5502 - 1064

Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	8550 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	1.59 mg of substance/m3
Final use:	Consumers.
Exposure method:	Ingestion.
Potential health effects:	Short term systemic effects.
DNEL :	32 mg/kg body weight/day
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	0.65 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Short term systemic effects.
DNEL :	13 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Short term local effects.
DNEL :	1.59 mg of substance/cm2
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	0.4 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term local effects.
DNEL :	0.68 mg of substance/cm2
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	2542 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	0.46 mg of substance/m3

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1,2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	2.5 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term local effects.
DNEL :	0.623 mg of substance/cm2

SD 5502 - 1064

Final use:	Consumers.
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	0.04 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	1.25 mg/kg body weight/day
Exposure method:	Dermal contact.
Potential health effects:	Long term local effects.
DNEL :	0.311 mg of substance/cm2

POLYALKYLAMINES (CAS: 39423-51-3)

Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	1.6 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	14 mg of substance/m3

Final use:	Consumers.
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	0.8 mg/kg body weight/day
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	3.48 mg of substance/m3

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Final use:	Workers.
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	20.1 mg of substance/m3
Exposure method:	Inhalation.
Potential health effects:	Short term local effects.
DNEL :	20.1 mg of substance/m3

Final use:	Man exposed via the environment.
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	0.526 mg/kg body weight/day

Predicted no effect concentration (PNEC):

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)	
Environmental compartment:	Soil.
PNEC :	0.18 mg/kg
Environmental compartment:	Fresh water.

SD 5502 - 1064

PNEC :	2.5 µg/l
Environmental compartment: PNEC :	Sea water. 2.5 µg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.22 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.14 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 1.64 mg/l

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Environmental compartment: PNEC :	Soil. 10 mg/kg
Environmental compartment: PNEC :	Fresh water. 1.6 µg/l
Environmental compartment: PNEC :	Sea water. 1.6 µg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.14 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.14 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 3.19 mg/l

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1,2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Environmental compartment: PNEC :	Soil. 0.0176 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.015 mg/l
Environmental compartment: PNEC :	Sea water. 0.0143 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.15 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.132 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.125 mg/kg
Environmental compartment:	Waste water treatment plant.

SD 5502 - 1064

PNEC :	7.5 mg/l
POLYALKYLAMINES (CAS: 39423-51-3)	
Environmental compartment: PNEC :	Soil. 0.002 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.0044 mg/l
Environmental compartment: PNEC :	Sea water. 0.00044 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.044 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.02 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.002 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)	
Environmental compartment: PNEC :	Soil. 1.121 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.06 mg/l
Environmental compartment: PNEC :	Sea water. 0.006 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.23 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 5.784 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.578 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 3.18 mg/l

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

SD 5502 - 1064

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

Mask with filter type A, B, E, K, P

Attention! If the protection group is insufficient.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :

Fluid liquid.

Color:

yellow

Important health, safety and environmental information

pH :

Not stated.

Slightly basic.

Boiling point/boiling range :

Not relevant.

Flash Point Interval :

FP > 100°C.

Vapour pressure (50°C) :

Not relevant.

Density :

0.97 ± 0.01 @ 20 °C

Water solubility :

Soluble.

Viscosity :

65 ± 15 mPa.s @ 25°C

SD 5502 - 1064

Melting point/melting range : Not relevant.
Self-ignition temperature : Not relevant.
Decomposition point/decomposition range : Not relevant.
% VOC : 0

9.2. Other information

Miscibility Alcohols, aromatic solvents

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Keep away from :
- strong oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- nitrogen oxide (NO)
- nitrogen dioxide (NO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Harmful if swallowed.

Harmful in contact with skin.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity :

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Oral route : LD50 = 1600 mg/kg
Species : Rat

ACIDE SALICYLIQUE (CAS: 69-72-7)

Oral route : LD50 = 891 mg/kg
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg
Species : Rat

Inhalation route (n/a) : LC50 > 0.9 mg/l

SD 5502 - 1064

	Species : Rat
PHENOL, STYRENATED (CAS: 61788-44-1)	
Oral route :	LD50 > 2000 mg/kg Species : Rat OECD Guideline 423 (Acute Oral toxicityAcute Toxic Class Method)
Dermal route :	LD50 > 2000 mg/kg Species : Rat OECD Guideline 402 (Acute Dermal Toxicity)
Inhalation route (n/a) :	LC50 = 4.9 mg/l OECD Guideline 403 (Acute Inhalation Toxicity)
META XYLENE DIAMINE (CAS: 1477-55-0)	
Oral route :	LD50 = 1040 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 = 2.4 mg/l Species : Rat
1,3-CYCLOHEXYLENEBIS (METHYLAMINE) (CAS: 2579-20-6)	
Oral route :	LD50 = 700 mg/kg Species : Rat
Dermal route :	LD50 = 1700 mg/kg Species : Rat
REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)	
Oral route :	LD50 = 2885.3 mg/kg Species : Rat
Dermal route :	LD50 = 2979.7 mg/kg Species : Rabbit
POLYALKYL AMINES (CAS: 39423-51-3)	
Oral route :	LD50 = 550 mg/kg Species : Rat
Dermal route :	LD50 > 1000 mg/kg Species : Rat
3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)	
Oral route :	LD50 = 1030 mg/kg Species : Rat
Dermal route :	LD50 > 2000 mg/kg Species : Rat OECD Guideline 402 (Acute Dermal Toxicity)
Inhalation route (n/a) :	LC50 > 5.01 mg/l Species : Rat OECD Guideline 403 (Acute Inhalation Toxicity)

SD 5502 - 1064

Skin corrosion/skin irritation :

PHENOL, STYRENATED (CAS: 61788-44-1)

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

META XYLENE DIAMINE (CAS: 1477-55-0)

Corrosivity :

Causes severe skin burns.

Species : Rat

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1,2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Corrosivity :

Causes severe skin burns.

Species : Rabbit

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

POLYALKYL AMINES (CAS: 39423-51-3)

Species : Rabbit

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Species : Rabbit

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitisation :

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Species : Rabbit

OECD Guideline 406 (Skin Sensitisation)

META XYLENE DIAMINE (CAS: 1477-55-0)

May cause an allergic skin reaction.

Local lymph node stimulation test :

Sensitiser.

OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity :

ACIDE SALICYLIQUE (CAS: 69-72-7)

Ames test (in vitro) :

Negative.

1,3-CYCLOHEXYLENEBIS (METHYLAMINE) (CAS: 2579-20-6)

Ames test (in vitro) :

Negative.

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Mutagenesis (in vivo) :

Negative.

PHENOL, STYRENATED (CAS: 61788-44-1)

Mutagenesis (in vivo) :

Negative.

OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Ames test (in vitro) :

Negative.

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

No mutagenic effect.

Mutagenesis (in vivo) :

Negative.

SD 5502 - 1064

META XYLENE DIAMINE (CAS: 1477-55-0)

No mutagenic effect.

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

No mutagenic effect.

Reproductive toxicant :

META XYLENE DIAMINE (CAS: 1477-55-0)

No toxic effect for reproduction

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

No toxic effect for reproduction

Study on development :

Species : Rat

OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

POLYALKYL AMINES (CAS: 39423-51-3)

Study on development :

Species : Rat

OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Specific target organ systemic toxicity - repeated exposure :

POLYALKYL AMINES (CAS: 39423-51-3)

Dermal route :

C > 160 mg/kg bodyweight/jour

Duration of exposure : 90 days

OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Species : Rat

META XYLENE DIAMINE (CAS: 1477-55-0)

Oral route :

C = 600 mg/kg bodyweight/day

Species : Rat

Duration of exposure : 28 days

OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Oral route :

C = 239 mg/kg bodyweight/day

Species : Rat

Duration of exposure : 28 days

OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

Dermal route :

C = 250 mg/kg bodyweight/day

Duration of exposure : 90 days

OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

11.1.2. Mixture

No toxicological data available for the mixture.

SD 5502 - 1064

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

POLYALKYL AMINES (CAS: 39423-51-3)

Algae toxicity : ECr50 = 1 mg/l
Duration of exposure : 72 h

1,3-CYCLOHEXYLENEBIS (METHYLAMINE) (CAS: 2579-20-6)

Fish toxicity : LC50 = 130 mg/l
Species : Leuciscus idus
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 64.7 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity : ECr50 = 58.4 mg/l
Duration of exposure : 72 h

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Fish toxicity : LC50 > 15 mg/l
Species : Others
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 = 80 mg/l
Species : Others
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Fish toxicity : LC50 = 110 mg/l
Species : Leuciscus idus
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 23 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC = 3 mg/l
Species : Daphnia magna
Duration of exposure : 21 days
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 > 50 mg/l
Species : Desmodesmus subspicatus
Duration of exposure : 72 h

SD 5502 - 1064

NOEC = 1.5 mg/l
Species : *Desmodesmus subspicatus*
Duration of exposure : 72 h
Other guideline

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Fish toxicity : LC50 = 180 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 17.5 mg/l
Duration of exposure : 48 h

NOEC = 0.8 mg/l
Duration of exposure : 14 days

Algae toxicity : ECr50 = 0.7 mg/l
Duration of exposure : 72 h

NOEC = 0.25 mg/l
Duration of exposure : 72 h

ACIDE SALICYLIQUE (CAS: 69-72-7)

Fish toxicity : LC50 = 1380 mg/l
Species : *Pimephales promelas*
Duration of exposure : 96 h
Other guideline

Crustacean toxicity : EC50 = 230 mg/l
Species : *Daphnia magna*
Duration of exposure : 24 h
OECD Guideline 202 (*Daphnia* sp. Acute Immobilisation Test)

NOEC = 10 mg/l
Species : *Daphnia magna*
Duration of exposure : 21 days

Algae toxicity : ECr50 > 100 mg/l
Species : *Desmodesmus subspicatus*
Duration of exposure : 72 h

POLYETHYLENEPOLYAMINES (CAS: 68131-73-7)

Fish toxicity : LC50 = 100 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 2.2 mg/l
Species : *Daphnia magna*
Duration of exposure : 48 h

Algae toxicity : ECr50 = 0.23 mg/l
Duration of exposure : 72 h

Aquatic plant toxicity : ECr50 = 319.3 mg/l
Duration of exposure : 48 h

SD 5502 - 1064

PHENOL, STYRENATED (CAS: 61788-44-1)

Fish toxicity : LC50 = 14.8 mg/l
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 <= 10 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC = 0.115 mg/l
Duration of exposure : 21 days
OECD Guideline 211 (Daphnia magna Reproduction Test)

Algae toxicity : ECr50 = 3.14 mg/l
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

META XYLENE DIAMINE (CAS: 1477-55-0)

Fish toxicity : LC50 = 87.6 mg/l
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 = 15.2 mg/l
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 = 20.3 mg/l
Species : Scenedesmus subspicatus
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

3,6,9,12-TETRA-AZATETRADECAMETHYLENEDIAMINE (CAS: 4067-16-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ACIDE SALICYLIQUE (CAS: 69-72-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

POLYETHYLENEDIAMINES (CAS: 68131-73-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

PHENOL, STYRENATED (CAS: 61788-44-1)

Biodegradability : Non-rapidly degradable.

META XYLENE DIAMINE (CAS: 1477-55-0)

SD 5502 - 1064

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

1,3-CYCLOHEXYLENEBIS (METHYLAMINE) (CAS: 2579-20-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

POLYALKYL AMINES (CAS: 39423-51-3)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

ACIDE SALICYLIQUE (CAS: 69-72-7)

Octanol/water partition coefficient : log K_{ow} = 2.25

PHENOL, STYRENATED (CAS: 61788-44-1)

Octanol/water partition coefficient : log K_{ow} ≤ 5.8
OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Bioaccumulation : BCF ≤ 190
OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

1,3-CYCLOHEXYLENEBIS (METHYLAMINE) (CAS: 2579-20-6)

Octanol/water partition coefficient : log K_{ow} = 0.783

REACTION PRODUCTS OF DI-, TRI AND TETRA-PROPOXYLATED PROPANE-1.2-DIOL WITH AMMONIA (CAS: 9046-10-0)

Octanol/water partition coefficient : log K_{ow} = 1.34

3-AMINOMETHYL-3,5,5-TRIMETHYL-CYCLOHEXYLAMINE (CAS: 2855-13-2)

Octanol/water partition coefficient : log K_{ow} = 0.99
OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

SD 5502 - 1064

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

07 01 08 * other still bottoms and reaction residues

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

2735

14.2. UN proper shipping name

UN2735=AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(3-aminomethyl-3,5,5-trimethyl-cyclohexylamine, polyalkyl amines)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	III	5 L	F-A,S-B	223 274	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	III	852	5 L	856	60 L	A3 A803	E1
	8	-	III	Y841	1 L	-	-	A3 A803	E1

SD 5502 - 1064

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Particular provisions :


No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H302 + H312	Harmful if swallowed or in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.